



# Listing and Technical Evaluation Report

Report No: 1407-10



Issue Date: August 11, 2014 Revision Date: December 9, 2023 Subject to Renewal: January 1, 2025

## DRYline® TSX Sheathing for Use as Draftstops in the IBC and IRC

## Trade Secret Report Holder:

## National Shelter Products, Inc.

Phone: 425-557-7968	Website: www.nationalshelter.com	Email: <a href="mailto:support@nationalshelter.com">support@nationalshelter.com</a>	
CSI Designations:			
DIVISION: 06 00 00 - WOOD, PLASTICS AND COMPOSITES			
Section: 06 02 00 - Design Information	Section: 06 12 00 - Structural P	Section: 06 12 00 - Structural Panels	
Section: 06 05 23 - Wood, Plastic, and Composite Faster	nings Section: 06 12 19 - Shear Wall	Section: 06 12 19 - Shear Wall Panels	
Section: 06 11 00 - Wood Framing	Section: 06 16 00 - Sheathing	Section: 06 16 00 - Sheathing	

## 1 Innovative Products Evaluated<sup>i</sup>

- 1.1 DRYline® TSX Structural Sheathing
  - 1.1.1 DRYline® TSX (Green) Structural Sheathing
  - 1.1.2 DRYline® TSX (Red) Structural Sheathing
  - 1.1.3 DRYline® TSX (Black) Structural Sheathing
  - 1.1.4 DRYline® TSX (Blue) Structural Sheathing

### 2 Product Description and Materials

- 2.1 DRYline® TSX Structural Sheathing panels are composed of multiple laminated plies consisting of highly water-resistant paperboard fibers adhered with a water-resistant adhesive.
- 2.2 Facings may be exposed to either polymer or aluminum foil.
  - 2.2.1 The panels are manufactured in four thicknesses:
    - 2.2.1.1 DRYline® TSX (Green) Structural Sheathing has a nominal thickness of 0.078" (1.98 mm).
    - 2.2.1.2 DRYline® TSX (Red) Structural Sheathing has a nominal thickness of 0.105" (2.67 mm).
    - 2.2.1.3 DRYline® TSX (Black) Structural Sheathing has a nominal thickness of 0.115" (2.92 mm).
    - 2.2.1.4 DRYline® TSX (Blue) Structural Sheathing has a nominal thickness of 0.137" (3.48 mm).





- 2.2.2 For material properties, see:
  - 2.2.2.1 DRYline® TSX (Green) Structural Sheathing: Report Number 1407-08
  - 2.2.2.2 DRYline® TSX (Red) Structural Sheathing: Report Number 1407-06
  - 2.2.2.3 DRYline® TSX (Black) Structural Sheathing: Report Number 1407-09
  - 2.2.2.4 DRYline® TSX (Blue) Structural Sheathing: Report Number 1407-07
- 2.3 Material Availability
  - 2.3.1 Width:
    - 2.3.1.1 Standard 48"
    - 2.3.1.2 48<sup>3</sup>/<sub>4</sub>"
    - 2.3.1.3 custom widths available upon request.
  - 2.3.2 Length:
- 2.3.2.1 Standard 96"
- 2.3.2.2 108"
- 2.3.2.3 120"
- 2.3.2.4 Custom lengths available upon request.
- 2.4 As needed, review material properties for design in Section **6** and to regulatory evaluation in Section **8**.

#### 3 Definitions

- 3.1 <u>New Materials</u><sup>ii</sup> are defined as building materials, equipment, appliances, systems, or methods of construction not provided for by prescriptive and/or legislatively adopted regulations, known as alternative materials.<sup>iii</sup> The <u>design strengths</u> and permissible stresses shall be established by tests<sup>iv</sup> and/or engineering analysis.<sup>v</sup>
- 3.2 <u>Duly Authenticated Reports</u><sup>vi</sup> and <u>Research Reports</u><sup>vii</sup> are test reports and related engineering evaluations, which are written by an <u>approved agency</u><sup>viii</sup> and/or an <u>approved source</u>.<sup>ix</sup>
  - 3.2.1 These reports contain intellectual property and/or trade secrets, which are protected by the <u>Defend Trade</u> <u>Secrets Act</u> (DTSA).<sup>x</sup>
- 3.3 An <u>approved agency</u> is "approved" when it is <u>ANAB ISO/IEC 17065 accredited</u>. DrJ Engineering, LLC (DrJ) is listed in the <u>ANAB directory</u>.
- 3.4 An <u>approved source</u> is "approved" when a professional engineer (i.e., <u>Registered Design Professional</u> [RDP]) is properly licensed to transact engineering commerce. The regulatory authority governing approved sources is the <u>state legislature</u> via its professional engineering regulations.<sup>xi</sup>
- 3.5 Testing and/or inspections conducted for this <u>Duly Authenticated Report</u> were performed by an <u>ISO/IEC 17025</u> accredited testing laboratory, an <u>ISO/IEC 17020</u> accredited inspection body, and/or a licensed <u>RDP</u>.
  - 3.5.1 The Center for Building Innovation (CBI) is ANAB<sup>xii</sup> ISO/IEC 17025 and ISO/IEC 17020 accredited.
- 3.6 The regulatory authority shall <u>enforce</u><sup>xiii</sup> the specific provisions of each legislatively adopted regulation. If there is a non-conformance, the specific regulatory section and language of the non-conformance shall be provided in <u>writing</u><sup>xiv</sup> stating the nonconformance and the path to its cure.
- 3.7 The regulatory authority shall accept <u>Duly Authenticated Reports</u> from an <u>approved agency</u> and/or an <u>approved</u> <u>source</u> with respect to the quality and manner of use of new materials or assemblies as provided for in regulations regarding the use of alternative materials, designs, or methods of construction.<sup>xv</sup>
- 3.8 ANAB is an <u>International Accreditation Forum</u> (IAF) <u>Multilateral Recognition Arrangement</u> (MLA) signatory where recognition of certificates, validation, and verification statements issued by conformity assessment bodies accredited by all other signatories of the IAF MLA with the appropriate scope, shall be approved.<sup>xvi</sup> Therefore, all ANAB ISO/IEC 17065 <u>Duly Authenticated Reports</u> are approval equivalent.<sup>xvii</sup>
- 3.9 Approval equity is a fundamental commercial and legal principle.xviii





### 4 Applicable Standards for the Listing; Regulations for the Regulatory Evaluation<sup>xix</sup>

#### 4.1 Regulations

- 4.1.1 IBC 15, 18, 21: International Building Code®
- 4.1.2 IRC 15, 18, 21: International Residential Code®

#### 5 Listed<sup>xx</sup>

5.1 A nationally recognized <u>testing laboratory</u> such as CBI, states that the materials, designs, methods of construction, and/or equipment have met nationally recognized standards and/or have been tested and found suitable for use in a specified manner.

#### 6 Tabulated Properties Generated from Nationally Recognized Standards

- 6.1 DRYline® TSX Structural Sheathing is used as an alternate draftstopping material in accordance with <u>IBC</u> Section 104.11 and <u>IRC Section R104.11</u>.
- 6.2 Use as an alternate material is based on the following code requirements regarding draft stops.
  - 6.2.1 Definitions (see <u>IBC Chapter 2</u> and <u>IRC Chapter 2</u>):

**DRAFT STOP**. A material, device or construction installed to restrict the movement of air within open spaces of concealed areas of building components such as crawl spaces, floor/ceiling assemblies, roof/ceiling assemblies and attics.

- 6.2.2 Based on the definition, a draft stop is used to restrict the movement of air within open spaces of concealed areas.
- 6.2.3 Fastening for draftstopping materials shall be adequate to support the weight of the draftstopping material and to minimize the movement of air. No other prescriptive fastening requirements are provided.
- 6.2.4 Draftstopping may be required in the following locations in accordance with the code sections referenced.
  - 6.2.4.1 IBC:
    - 6.2.4.1.1 For continuity at fire partitions between the ceiling and deck above, either fireblocking or draftstopping may be required (see <u>IBC Section 708.4.2</u> for specific requirements and exceptions). In floors of structures of combustible construction, draftstopping is required in the locations required by <u>IBC Section 708.4.2</u>, per <u>IBC Section 718.3</u>. In addition, in other than Group R occupancies, the floor/ceiling assemblies shall be subdivided such that the floor areas do not exceed 1,000 sq. ft. Buildings equipped with an automatic fire sprinkler system in accordance with <u>IBC Section 903.3.1.1</u> are not required to comply with this section.
    - 6.2.4.1.2 In attics of structures of combustible construction, draftstopping is required in the locations required by <u>IBC Section 708.4.2</u>, per <u>IBC Section 718.4</u>. In addition, in other than Group R occupancies, the attics spaces and combustible concealed roof spaces shall be subdivided such that the horizontal areas do not exceed 3,000 sq. ft. Buildings equipped with an automatic fire sprinkler system in accordance with <u>IBC Section 903.3.1.1</u> are not required to comply with this section.





### 6.2.4.2 IRC:

- 6.2.4.2.1 In combustible construction where there is usable space both above and below the concealed space of a floor/ceiling assembly, draftstopping is required to subdivide the space into areas no greater than 1,000 sq. ft., per <u>IRC Section R302.12</u>. The draftstopping shall be installed where the ceiling is suspended under the floor framing and where the floor framing is constructed of truss-type open-web or perforated members.
- 6.2.4.2.2 In accordance with <u>IRC Section R302.3</u>, where the fire separation wall in two-family buildings does not extend through the attic, draftstopping is required in the roof/ceiling assembly above the fire separation wall. In this case, the ceiling must be protected by no less than <sup>5</sup>/<sub>8</sub>" Type X gypsum board and the framing supporting the ceiling must be protected by not less than <sup>1</sup>/<sub>2</sub>" gypsum board or equivalent.
- 6.3 Draft stop material requirements are similar in the IBC and IRC. However, the IBC includes a few more prescribed products.
  - 6.3.1 IBC Section 718.3.1:

#### Draftstopping materials.

Draftstopping materials shall not be less than 1/2-inch (12.7 mm) gypsum board, 3/8-inch (9.5 mm) wood structural panel, 3/8-inch (9.5 mm) particleboard, 1-inch (25-mm) nominal lumber, cement fiberboard, batts or blankets of mineral wool or glass fiber, or other approved materials adequately supported. The integrity of draftstops shall be maintained.

#### 6.3.2 IRC Section R302.12.1:

#### Draftstopping materials.

Draftstopping materials shall not be less than 1/2-inch (12.7 mm) gypsum board, 3/8-inch (9.5 mm) wood structural panels or other approved materials adequately supported. Draftstopping shall be installed parallel to the floor framing members unless otherwise approved by the building official. The integrity of the draftstops shall be maintained.

- 6.4 DRYline® TSX Structural Sheathing meets the requirements for draft stop materials for the following reasons:
  - 6.4.1 As installed per the manufacturer instructions, it complies with the code definition with respect to "*restricting the movement of air*."
  - 6.4.2 As installed per the manufacturer installation instructions, DRYline® TSX Structural Sheathing is adequately supported and will remain in place.
  - 6.4.3 Batt or blanket mineral wool or glass fiber only require that they be adequately supported and restrict the movement of air. These products are air-permeable and restrict the passage of air to a lesser degree than DRYline® TSX Structural Sheathing.
- 6.5 Draft stops are not intended to restrict the passage of heat or flame. The code addresses heat and flame impingement with fire-resistance rated assemblies, thermal barriers, and ignition barriers.
- 6.6 Where the application falls outside of the performance evaluation, conditions of use, and/or installation requirements set forth herein, alternative techniques shall be permitted in accordance with accepted engineering practice and experience. This includes but is not limited to the following areas of engineering: mechanics or materials, structural, building science, and fire science.





### 7 Certified Performance<sup>xxi</sup>

- 7.1 All construction methods shall conform to accepted engineering practices to ensure durable, livable, and safe construction and shall demonstrate acceptable workmanship reflecting journeyman quality of work of the various trades.<sup>xxii</sup>
- 7.2 The strength and rigidity of the component parts and/or the integrated structure shall be determined by engineering analysis or by suitable load tests to simulate the actual loads and conditions of application that occur.<sup>xxiii</sup>

### 8 Regulatory Evaluation and Accepted Engineering Practice

- 8.1 DRYline® TSX Structural Sheathing complies with the following legislatively adopted regulations and/or accepted engineering practice for the following reasons:
- 8.1.1 Evaluation of DRYline® TSX (Red, Black, Blue, and Green) Structural Sheathing used as draft stop material based on IBC and IRC draftstopping provisions and definitions.
- 8.2 Any building code, regulation, and/or accepted engineering evaluations (i.e., research reports, duly authenticated reports, etc.) that are conducted for this report were performed by DrJ Engineering, LLC (DrJ), an ISO/IEC 17065 accredited certification body and a professional engineering company operated by RDP/approved sources. DrJ is qualified<sup>xxiv</sup> to practice product and regulatory compliance services within its scope of accreditation and engineering expertise, respectively.
- 8.3 Engineering evaluations are conducted with DrJ's ANAB <u>accredited ICS code scope</u> of expertise, which are also its areas of professional engineering competence.
- 8.4 Any regulation specific issues not addressed in this section are outside the scope of this report.

#### 9 Installation

- 9.1 Installation shall comply with the approved construction documents, the manufacturer installation instructions, this report, and the applicable building code.
- 9.2 In the event of a conflict between the manufacturer installation instructions and this report, the more restrictive shall govern.
- 9.3 A copy of the manufacturer published installation instructions shall be available at all times on the jobsite during installation.

#### 9.4 Orientation

- 9.4.1 DRYline® TSX Structural Sheathing is permitted to be installed in the vertical or horizontal orientation on framing with all joints backed by studs, plates, or blocks. For joints not backed by studs, plates, or blocks, the joint shall be taped to ensure impedance of air movement.
- 9.5 Fastener Spacing and Edge Distance
  - 9.5.1 Fastener edge distance is a minimum of 3/8" (9.5 mm).
  - 9.5.2 Always fasten staples parallel to the framing member.
  - 9.5.3 Fasteners shall be spaced to ensure adequate support of DRYline® TSX Structural Sheathing to remain in place.

#### 9.6 *Treatment of Joints*

- 9.6.1 Sheathing joints may be either butted or overlapped.
- 9.6.2 Lapped joints shall be overlapped by at least <sup>3</sup>/<sub>4</sub>" (19 mm) and fastened with a single row of fasteners.
- 9.6.3 Butt joints shall be placed over framing members and fastened with a single row of fasteners at each panel edge and shall be installed with a small gap (1/16" to 1/8") between panels.





#### **10** Substantiating Data

- 10.1 Information contained herein may include the result of testing and/or data analysis by sources that are <u>approved agencies</u>, <u>approved sources</u>, and/or <u>RDPs</u>. Accuracy of external test data and resulting analysis is relied upon.
- 10.2 Where pertinent, testing and/or engineering analysis are based upon provisions that have been codified into law through state or local adoption of regulations and standards. The developers of these regulations and standards are responsible for the reliability of published content. DrJ's engineering practice may use a regulation-adopted provision as the control. A regulation-endorsed control versus a simulation of the conditions of application to occur establishes a new material as <u>being equivalent</u> to the regulatory provision in terms of quality, <u>strength</u>, effectiveness, <u>fire resistance</u>, durability, and safety.
- 10.3 The accuracy of the provisions provided herein may be reliant upon the published properties of raw materials, which are defined by the grade mark, grade stamp, mill certificate, or <u>duly authenticated reports</u> from <u>approved</u> <u>agencies</u> and/or <u>approved sources</u> provided by the supplier. These are presumed to be minimum properties and relied upon to be accurate. The reliability of DrJ's engineering practice, as contained in this <u>duly</u> <u>authenticated report</u>, may be dependent upon published design properties by others.
- 10.4 Testing and engineering analysis: The strength, rigidity, and/or general performance of component parts and/or the integrated structure are determined by suitable tests that simulate the actual conditions of application that occur and/or by accepted engineering practice and experience.<sup>xxv</sup>
- 10.5 Where additional condition of use and/or regulatory compliance information is required, please search for DRYline® TSX Structural Sheathing on the <u>DrJ Certification</u> website.

#### 11 Findings

- 11.1 As outlined in Section **6**, DRYline® TSX Structural Sheathing has performance characteristics that were tested and/or meet applicable regulations and is suitable for use pursuant to its specified purpose.
- 11.2 When used and installed in accordance with this <u>duly authenticated report</u> and the manufacturer installation instructions, DRYline® TSX Structural Sheathing shall be approved for the following applications:
  - 11.2.1 Use as a draftstopping material when installed in accordance with the manufacturer installation instructions and this report.
- 11.3 Any application specific issues not addressed herein can be engineered by an <u>RDP</u>. Assistance with engineering is available from National Shelter Products, Inc.
- 11.4 <u>IBC Section 104.11</u> (IRC Section R104.11 and <u>IFC Section 104.10</u> xxvi are similar) in pertinent part states:

**104.11** Alternative materials, design and methods of construction and equipment. The provisions of this code are not intended to prevent the installation of any material or to prohibit any design or method of construction not specifically prescribed by this code. Where the alternative material, design or method of construction is not approved, the building official shall respond in writing, stating the reasons the alternative was not approved.

- 11.5 Approved:xxvii Building regulations require that the building official shall accept duly authenticated reports.xxviii
  - 11.5.1 An approved agency is "approved" when it is ANAB ISO/IEC 17065 accredited.
  - 11.5.2 An <u>approved source</u> is "approved" when an <u>RDP</u> is properly licensed to transact engineering commerce.
  - 11.5.3 Federal law, <u>Title 18 US Code Section 242</u>, requires that where the alternative product, material, service, design, assembly, and/or method of construction is not approved, the building official shall respond in writing, stating the reasons why the alternative was not approved. Denial without written reason deprives a protected right to free and fair competition in the marketplace.





- 11.6 DrJ is a licensed engineering company, employs licensed RDPs and is an <u>ANAB-Accredited Product</u> <u>Certification Body</u> – <u>Accreditation #1131</u>.
- 11.7 Through the <u>IAF Multilateral Agreements</u> (MLA), this <u>Duly Authenticated Report</u> can be used to obtain product approval in any jurisdiction or <u>country</u> because all ANAB ISO/IEC 17065 <u>Duly Authenticated Reports</u> are equivalent.<sup>xxix</sup>

## 12 Conditions of Use

- 12.1 Material properties shall not fall outside the boundaries defined in Section 6.
- 12.2 As defined in Section **6**, where material and/or engineering mechanics properties are created for load resisting design purposes, the resistance to the applied load shall not exceed the ability of the defined properties to resist those loads using the principles of accepted engineering practice.
- 12.3 As listed herein, DRYline® TSX Structural Sheathing shall be used:
  - 12.3.1 In accordance with the manufacturer installation instructions, the applicable building code, and this report.
- 12.4 When required by adopted legislation and enforced by the <u>building official</u>, also known as the authority having jurisdiction (AHJ) in which the project is to be constructed:
  - 12.4.1 Any calculations incorporated into the construction documents shall conform to accepted engineering practice and, when prepared by an <u>approved source</u>, shall be approved when signed and sealed.
  - 12.4.2 This report and the installation instructions shall be submitted at the time of permit application.
  - 12.4.3 These innovative products has an internal quality control program and a third-party quality assurance program.
  - 12.4.4 At a minimum, these innovative products shall be installed per Section 9 of this report.
  - 12.4.5 The review of this report by the AHJ shall comply with IBC Section 104 and IBC Section 105.4.
  - 12.4.6 These innovative products have an internal quality control program and a third party quality assurance program in accordance with <u>IBC Section 104.4</u>, <u>IBC Section 110.4</u>, <u>IBC Section 1703</u>, <u>IRC Section R104.4</u>, and <u>IRC Section R109.2</u>.
  - 12.4.7 The application of these innovative products in the context of this report, is dependent upon the accuracy of the construction documents, implementation of installation instructions, inspection as required by <u>IBC</u> <u>Section 110.3</u>, <u>IRC Section R109.2</u>, and any other regulatory requirements that may apply.
- 12.5 The approval of this report by the AHJ shall comply with <u>IBC Section 1707.1</u>, where legislation states in part, "the <u>building official</u> shall accept duly authenticated reports from <u>approved agencies</u> in respect to the quality and manner of <u>use</u> of new material or assemblies as provided for in <u>Section 104.11</u>," all of <u>IBC Section 104</u> and <u>IBC Section 105.4</u>.
- 12.6 <u>Design loads</u> shall be determined in accordance with the regulations adopted by the jurisdiction in which the project is to be constructed and/or by the building designer (i.e., <u>owner</u> or RDP).
- 12.7 The actual design, suitability, and use of this report for any particular building, is the responsibility of the <u>owner</u> or the authorized agent of the owner.





## 13 Identification

- 13.1 The innovative products listed in Section **1.1** are identified by a label on the board or packaging material bearing the manufacturer name, product name, this report number, and other information to confirm code compliance.
- 13.2 Additional technical information can be found at <u>www.nationalshelter.com</u>.

#### 14 Review Schedule

- 14.1 This report is subject to periodic review and revision. For the latest version, visit <u>dricertification.org</u>.
- 14.2 For information on the status of this report, please contact <u>DrJ Certification</u>.

### 15 Approved for Use Pursuant to U.S. and International Legislation Defined in Appendix A

15.1 DRYline® TSX Structural Sheathing is included in this report published by an approved agency that is concerned with evaluation of products or services, maintains periodic inspection of the production of listed materials or periodic evaluation of services. This report states either that the material, product, or service meets recognized standards or has been tested and found suitable for a specified purpose. This report meets the legislative intent and definition of being acceptable to the AHJ.





## Appendix A

## 1 Legislation that Authorizes AHJ Approval

- 1.1 **Fair Competition**: <u>State legislatures</u> have adopted Federal regulations for the examination and approval of building code referenced and alternative products, materials, designs, services, assemblies and/or methods of construction that:
  - 1.1.1 Advance Innovation,
  - 1.1.2 Promote competition so all businesses have the opportunity to compete on price and quality in an open market on a level playing field unhampered by anticompetitive constraints, and
  - 1.1.3 Benefit consumers through lower prices, better quality and greater choice.
- 1.2 **Adopted Legislation**: The following local, state and federal regulations affirmatively authorize these innovative products to be approved by AHJs, delegates of building departments and/or delegates of an agency of the federal government:
  - 1.2.1 Interstate commerce is governed by the <u>Federal Department of Justice</u> to encourage the use of innovative products, materials, designs, services, assemblies and/or methods of construction. The goal is to "protect economic freedom and opportunity by promoting free and fair competition in the marketplace."
  - 1.2.2 <u>Title 18 US Code Section 242</u> affirms and regulates the right of individuals and businesses to freely and fairly have new products, materials, designs, services, assemblies and/or methods of construction approved for use in commerce. Disapproval of alternatives shall be based upon non-conformance with respect to specific provisions of adopted legislation and shall be provided in writing <u>stating the reasons why</u> the alternative was not approved, with reference to the specific legislation violated.
  - 1.2.3 The <u>federal government</u> and each state have a <u>public records act</u>. In addition, each state also has legislation that mimics the federal <u>Defend Trade Secrets Act 2016</u> (DTSA),<sup>xxx</sup> where providing test reports, engineering analysis and/or other related IP/TS is subject to <u>prison of not more than ten years</u><sup>xxxi</sup> and/or a <u>\$5,000,000 fine or 3 times the value of</u><sup>xxxii</sup> the Intellectual Property (IP) and Trade Secrets (TS).
    - 1.2.3.1 Compliance with public records and trade secret legislation requires approval through the use of Listings, certified reports, Technical Evaluation Reports, duly authenticated reports and/or research reports prepared by approved agencies and/or approved sources.
  - 1.2.4 For <u>new materials</u> xxiii that are not specifically provided for in any regulation, the <u>design strengths and</u> <u>permissible stresses</u> shall be established by <u>tests</u>, where <u>suitable load tests simulate the actual loads and</u> <u>conditions of application that occur</u>.
  - 1.2.5 The <u>design strengths and permissible stresses</u> of any structural material shall <u>conform</u> to the specifications and methods of design using accepted engineering practice.<sup>xxxiv</sup>
  - 1.2.6 The commerce of <u>approved sources</u> (i.e., registered PEs) is regulated by <u>professional engineering</u> <u>legislation</u>. Professional engineering <u>commerce shall always be approved</u> by AHJs, except where there is evidence provided in writing, that specific legislation has been violated by an individual registered PE.
  - 1.2.7 The AHJ shall accept <u>duly authenticated reports</u> from <u>approved agencies</u> in respect to the quality and manner of use of new materials or assemblies as provided for in <u>IBC Section 104.11</u>.<sup>xxxv</sup>





- 1.3 Approved xxxvi by Los Angeles: The Los Angeles Municipal Code (LAMC) states in pertinent part that the provisions of LAMC are not intended to prevent the use of any material, device, or method of construction not specifically prescribed by LAMC. The Department shall use Part III, Recognized Standards in addition to Part II, Uniform Building Code Standards of <u>Division 35</u>, <u>Article 1</u>, <u>Chapter IX</u> of the LAMC in evaluation of products for approval where such standard exists for the product or the material and may use other approved standards that apply. Whenever tests or certificates of any material or fabricated assembly are required by <u>Chapter IX</u> of the LAMC, such tests or certification shall be made by a <u>testing agency</u> approved by the Superintendent of Building to conduct such tests or provide such certifications. The testing agency shall publish the scope and limitation(s) of the listed material or fabricated assembly.<sup>xxxvii</sup> The Superintendent of Building <u>Approved Testing Agency</u> <u>Roster</u> is provided by the Los Angeles Department of Building and Safety (LADBS). The Center for Building Innovation (CBI) Certificate of Approval License is <u>TA24945</u>. Tests and certifications found in a <u>DrJ Listing</u> are LAMC approved. In addition, the Superintendent of Building shall accept <u>duly authenticated reports</u> from <u>approved agencies</u> in respect to the quality and manner of use of new materials or assemblies as provided for in the <u>California Building Code</u> (CBC) <u>Section 1707.1</u>.<sup>xxxviii</sup>
- 1.4 Approved by Chicago: The Municipal Code of Chicago (MCC) states in pertinent part that an Approved Agency is a Nationally Recognized Testing Laboratory (NRTL) acting within its recognized scope and/or a certification body accredited by the American National Standards Institute (ANSI) acting within its accredited scope. Construction materials and test procedures shall conform to the applicable standards listed in the MCC. Sufficient technical data shall be submitted to the building official to substantiate the proposed use of any product, material, service, design, assembly and/or method of construction not specifically provided for in the MCC. This technical data shall consist of research reports from approved sources (i.e., MCC defined Approved Agencies).
- 1.5 Approved by New York City: The <u>2022 NYC Building Code</u> (NYCBC) states in part that an <u>approved agency</u> shall be deemed<sup>xxxix</sup> an approved testing agency via <u>ISO/IEC 17025 accreditation</u>, an approved inspection agency via <u>ISO/IEC 17020 accreditation</u> and an approved product evaluation agency via <u>ISO/IEC 17065</u> <u>accreditation</u>. Accrediting agencies, other than federal agencies, must be members of an internationally recognized cooperation of laboratory and inspection accreditation bodies subject to a mutual recognition agreement<sup>xi</sup> (i.e., <u>ANAB</u>, <u>International Accreditation Forum</u> (IAF), etc.).
- 1.6 **Approved by Florida**: <u>Statewide approval</u> of products, methods, or systems of construction shall be approved, without further evaluation by:
  - 1.6.1 A certification mark or listing of an approved certification agency,
  - 1.6.2 A test report from an approved testing laboratory,
  - 1.6.3 A product evaluation report based upon testing or comparative or rational analysis, or a combination thereof, from an approved product evaluation entity, or
  - 1.6.4 A product evaluation report based upon testing, comparative or rational analysis, or a combination thereof, developed, signed and sealed by a professional engineer or architect, licensed in Florida.
- 1.7 For local product approval, products or systems of construction shall demonstrate compliance with the structural wind load requirements of the Florida Building Code (FBC) through one of the following methods;
  - 1.7.1 A certification mark, listing or label from a commission-approved certification agency indicating that the product complies with the code,
  - 1.7.2 A test report from a commission-approved testing laboratory indicating that the product tested complies with the code,
  - 1.7.3 A product-evaluation report based upon testing, comparative or rational analysis, or a combination thereof, from a commission-approved product evaluation entity which indicates that the product evaluated complies with the code,
  - 1.7.4 A product-evaluation report or certification based upon testing or comparative or rational analysis, or a combination thereof, developed and signed and sealed by a Florida professional engineer or Florida registered architect, which indicates that the product complies with the code, or
  - 1.7.5 A statewide product approval issued by the Florida Building Commission.





- 1.8 The <u>Florida Department of Business and Professional Regulation</u> (DBPR) website provides a listing of companies certified as a <u>Product Evaluation Agency</u> (i.e., EVLMiami 13692), a <u>Product Certification Agency</u> (i.e., CER10642) and as a <u>Florida Registered Engineer</u> (i.e., ANE13741).
- 1.9 **Approved by Miami-Dade County (i.e., Notice of Acceptance [NOA])**: A Florida statewide approval is an NOA. An NOA is a Florida local product approval. By Florida law, Miami-Dade County shall accept the statewide and local Florida Product Approval as provided for in Florida legislation <u>553.842</u> and <u>553.8425</u>.
- 1.10 Approved by New Jersey: Pursuant to the 2018 Building Code of New Jersey in <u>IBC Section 1707.1</u> <u>General</u>, x<sup>ii</sup> it states: "In the absence of approved rules or other approved standards, the building official shall accept duly authenticated reports from <u>approved agencies</u> in respect to the quality and manner of use of new materials or assemblies as provided for in the administrative provisions of the Uniform Construction Code (<u>N.J.A.C. 5:23</u>)". <sup>xiii</sup> Furthermore N.J.A.C 5:23-3.7 states: "Municipal approvals of alternative materials, equipment, or methods of construction."
  - 1.10.1 **Approvals**: Alternative materials, equipment, or methods of construction shall be approved by the appropriate subcode official provided the proposed design is satisfactory and that the materials, equipment, or methods of construction are suitable for the intended use and are at least the equivalent in quality, strength, effectiveness, fire resistance, durability and safety of those conforming with the requirements of the regulations.
    - 1.10.1.1 A field evaluation label and report or letter issued by a nationally recognized testing laboratory verifying that the specific material, equipment, or method of construction meets the identified standards or has been tested and found to be suitable for the intended use, shall be accepted by the appropriate subcode official as meeting the requirements of the above.
    - 1.10.1.2 Reports of engineering findings issued by nationally recognized evaluation service programs such as but not limited to, the Building Officials and Code Administrators (BOCA), the International Conference of Building Officials (ICBO), the Southern Building Code Congress International (SBCCI), the International Code Council (ICC) and the National Evaluation Service, Inc., shall be accepted by the appropriate subcode official as meeting the requirements of the above.
  - 1.10.2 The <u>New Jersey Department of Community Affairs</u> has confirmed that technical evaluation reports, from any accredited entity listed by <u>ANAB</u>, meets the requirements of item the previous paragraph, given that the listed entities are no longer in existence and/or do not provide "*reports of engineering findings*".
- 1.11 Approved by the Code of Federal Regulations Manufactured Home Construction and Safety Standards: Pursuant to Title 24, Subtitle B, Chapter XX, <u>Part 3282.14 xiiii</u> and <u>Part 3280</u>, xiv the Department encourages innovation and the use of new technology in manufactured homes. The design and construction of a manufactured home shall conform to the provisions of Part 3282 and Part 3280 where key approval provisions in mandatory language follow:
  - 1.11.1 "All construction methods shall be in conformance with accepted engineering practices"
  - 1.11.2 "The strength and rigidity of the component parts and/or the integrated structure shall be determined by engineering analysis or by suitable load tests to simulate the actual loads and conditions of application that occur."
  - 1.11.3 *"The design stresses of all materials shall conform to accepted engineering practice."*





- 1.12 **Approval by US, Local and State Jurisdictions in Genera**l: In all other local and state jurisdictions, the adopted building code legislation states in pertinent part that:
  - 1.12.1 For <u>new materials</u> that are not specifically provided for in this code, the <u>design strengths and permissible</u> <u>stresses</u> shall be established by tests.<sup>xlv</sup>
  - 1.12.2 For innovative <u>alternatives</u> and/or methods of construction, the building official shall accept <u>duly</u> <u>authenticated reports</u> from <u>approved agencies</u> with respect to the quality and manner of use of <u>new</u> <u>materials or assemblies</u>.<sup>xlvi</sup>
    - 1.12.2.1 An <u>approved agency</u> is "approved" when it is <u>ANAB ISO/IEC 17065 accredited</u>. DrJ Engineering, LLC (DrJ) is in the <u>ANAB directory</u>.
    - 1.12.2.2 An <u>approved source</u> is "approved" when an <u>RDP</u> is properly licensed to transact engineering commerce. The regulatory authority governing approved sources is the <u>state legislature</u> via its professional engineering regulations.<sup>xlvii</sup>
  - 1.12.3 The <u>design strengths and permissible stresses</u> of any structural material...shall conform to the specifications and methods of design of accepted engineering practice performed by an <u>approved</u> <u>source</u>.<sup>xlviii</sup>
- 1.13 **Approval by International Jurisdictions**: The <u>USMCA</u> and <u>GATT</u> agreements provide for approval of innovative materials, designs, services and/or methods of construction through the <u>Agreement on Technical</u> <u>Barriers to Trade</u> and the <u>IAF Multilateral Recognition Arrangement</u> (MLA), where these agreements:
  - 1.13.1 State that <u>conformity assessment procedures</u> (i.e., ISO/IEC 17020, 17025, 17065, etc.) are prepared, adopted and applied so as to grant access for suppliers of like products originating in the territories of other Members under conditions no less favourable than those accorded to suppliers of like products of national origin or originating in any other country, in a comparable situation.
  - 1.13.2 **Approved**: The <u>purpose of the MLA</u> is to ensure mutual recognition of accredited certification and validation/verification statements between signatories to the MLA and subsequently, acceptance of accredited certification and validation/verification statements in many markets based on one accreditation for the timely approval of innovative materials, designs, services and/or methods of construction.
  - 1.13.3 ANAB is an <u>IAF-MLA</u> signatory where recognition of certificates, validation and verification statements issued by conformity assessment bodies accredited by all other signatories of the IAF MLA, with the appropriate scope, shall be approved.<sup>xlix</sup>
  - 1.13.4 Therefore, all ANAB ISO/IEC 17065 Duly Authenticated Reports are approval equivalent.<sup>1</sup>
- 1.14 Approval equity is a fundamental commercial and legal principle.<sup>li</sup>





## Notes

#### <sup>i</sup> For more information, visit drjcertification.org or call us at 608-310-6748.

- https://up.codes/viewer/wyoming/ibc-2021/chapter/17/special-inspections-and-tests#1702
- Alternative Materials, Design and Methods of Construction and Equipment: The provisions of any regulation code are not intended to prevent the installation of any material or to prohibit any design or method of construction not specifically prescribed by a regulation. Please review <u>https://www.justice.gov/atr/mission and</u> <u>https://up.codes/viewer/colorado/ibc-2021/chapter/1/scope-and-administration#104.11</u>
- https://up.codes/viewer/wyoming/ibc-2021/chapter/17/special-inspections-andtests#1706:~:text=the%20design%20strengths%20and%20permissible%20stresses%20shall%20be%20established%20by%20tests%20as
- The design strengths and permissible stresses of any structural material shall conform to the specifications and methods of design of accepted engineering practice. <u>https://up.codes/viewer/wyoming/ibc-2021/chapter/17/special-inspections-and-</u> tests#1706:~:text=shall%20conform%20to%20the%20specifications%20and%20methods%20of%20design%20of%20accepted%20engineering%20practice
- https://up.codes/viewer/wyoming/ibc-2021/chapter/17/special-inspections-andtests#1707.1:~:text=the%20building%20official%20shall%20accept%20duly%20authenticated%20reports%20from%20approved%20agencies
- vii https://up.codes/viewer/wyoming/ibc-2021/chapter/17/special-inspections-and-tests#1703.4.2
- viii https://up.codes/viewer/wyoming/ibc-2021/chapter/2/definitions#approved\_agency
- ix https://up.codes/viewer/wyoming/ibc-2021/chapter/2/definitions#approved\_source
- \* <u>https://www.law.cornell.edu/uscode/text/18/1832</u> (b) Any organization that commits any offense described in subsection (a) shall be fined not more than the greater of \$5,000,000 or 3 times the value of the stolen trade secret to the organization, including expenses for research and design and other costs of reproducing the trade secret that the organization has thereby avoided. The <u>federal government</u> and each state have a <u>public records act</u>. To follow DTSA and comply state public records and trade secret legislation requires approval through <u>ANAB ISO/IEC 17065 accredited certification bodies</u> or <u>approved sources</u>. For more information, please review this website: <u>Intellectual Property and Trade Secrets</u>.
- xi https://www.nspe.org/resources/issues-and-advocacy/professional-policies-and-position-statements/regulation-professional AND https://apassociation.org/list-of-engineeringboards-in-each-state-archive/
- xii https://www.cbitest.com/accreditation/
- https://up.codes/viewer/colorado/ibc-2021/chapter/1/scope-and-administration#104:~:text=to%20enforce%20the%20provisions%20of%20this%20code
- xiv https://up.codes/viewer/colorado/ibc-2021/chapter/1/scope-and-

administration#104.11:~:text=Where%20the%20alternative%20material%2C%20design%20or%20method%20of%20construction%20is%20not%20approved%2C%20the%20buildi ng%20official%20shall%20respond%20in%20writing%2C%20stating%20the%20reasons%20why%20the%20alternative%20was%20not%20approved AND https://up.codes/viewer/colorado/ibc-2021/chapter/1/scope-and-

administration#105.3.1:~:text=If%20the%20application%20or%20the%20construction%20documents%20do%20not%20conform%20to%20the%20requirements%20of%20pertinen t%20laws%2C%20the%20building%20official%20shall%20reject%20such%20application%20in%20writing%2C%20stating%20the%20reasons%20therefore

- https://up.codes/viewer/colorado/ibc-2021/chapter/17/special-inspections-andtests#1707.1:~:text=the%20building%20official%20shall%20accept%20duly%20authenticated%20reports%20from%20approved%20agencies%20in%20respect%20to%20the%20 guality%20and%20manner%20of%20use%20of%20new%20materials%20or%20assemblies%20as%20provided%20for%20in%20Section%20104.11
- https://iaf.nu/en/about-iafmla/#:~:text=it%20is%20required%20to%20recognise%20certificates%20and%20validation%20and%20verification%20statements%20issued%20by%20conformity%20assessmen t%20bodies%20accredited%20by%20all%20other%20signatories%20of%20the%20IAF%20MLA%2C%20with%20the%20appropriate%20scope
- xvii True for all ANAB accredited product evaluation agencies and all International Trade Agreements.
- xviii https://www.justice.gov/crt/deprivation-rights-under-color-law AND https://www.justice.gov/atr/mission
- xix Unless otherwise noted, all references in this report are from the 2021 version of the codes and the standards referenced therein. This material, product, design, service and/or method of construction also complies with the 2000-2021 versions of the referenced codes and the standards referenced therein.
- https://www.ecfr.gov/current/title-24/subtitle-B/chapter-XX/part-3280#p-3280.2(Listed%20or%20certified); https://up.codes/viewer/colorado/ibc-2021/chapter/2/definitions#listed
  AND https://up.codes/viewer/colorado/ibc-2021/chapter/2/definitions#labeled
- xi https://up.codes/viewer/colorado/ibc-2021/chapter/17/special-inspections-and-tests#1703.4
- xxii <u>https://www.ecfr.gov/current/title-24/subtitle-B/chapter-XX/part-3280#:~:text=All%20construction%20methods%20shall%20be%20in%20conformance%20with%20accepted%20engineering%20practices%20to%20insure%20durable%2C%20liv able%2C%20and%20safe%20housing%20and%20shall%20demonstrate%20acceptable%20workmanship%20reflecting%20journeyman%20quality%20of%20work%20of%20the% 20various%20trades</u>
- xiii <u>https://www.ecfr.gov/current/title-24/subtitle-B/chapter-XX/part-3280#:~:text=The%20strength%20and%20rigidity%20of%20the%20component%20parts%20and/or%20the%20integrated%20structure%20shall%20be%20determined%20by%20 engineering%20analysis%20or%20by%20suitable%20load%20tests%20to%20simulate%20the%20actual%20loads%20and%20conditions%20of%20application%20that%20occur</u>
- xiv Qualification is performed by a legislatively defined <u>Accreditation Body</u>. <u>ANSI National Accreditation Board (ANAB)</u> is the largest independent accreditation body in North America and provides services in more than 75 countries. <u>DrJ</u> is an ANAB accredited <u>product certification body</u>.
- xxv See Code of Federal Regulations (CFR) Title 24 Subtitle B Chapter XX Part 3280 for definition.
- xxvi 2018 IFC Section 104.9
- Approved is an adjective that modifies the noun after it. For example, Approved Agency means that the Agency is accepted officially as being suitable in a particular situation. This example conforms to IBC/IRC/IFC Section 201.4 where the building code authorizes sentences to have an ordinarily accepted meaning such as the context implies.
- xxviii https://up.codes/viewer/wyoming/ibc-2021/chapter/17/special-inspections-and-tests#1707.1





- xxix Multilateral approval is true for all ANAB accredited product evaluation agencies and all International Trade Agreements.
- xxx <u>http://www.drjengineering.org/AppendixC</u> AND <u>https://www.drjcertification.org/cornell-2016-protection-trade-secrets</u>
- xxxi <u>https://www.law.cornell.edu/uscode/text/18/1832#:~:text=imprisoned%20not%20more%20than%2010%20years</u>
- xxxii https://www.law.cornell.edu/uscode/text/18/1832#:~:text=Any%20organization%20that,has%20thereby%20avoided
- xxxiii <u>https://up.codes/viewer/wyoming/ibc-2021/chapter/17/special-inspections-and-tests#1706.2</u>
- xxxiv IBC 2021, Section 1706.1 Conformance to Standards
- IBC 2021, Section 1707 Alternative Test Procedure, 1707.1 General
- xxxvi See Section 11.5 for the distilled building code definition of Approved.
- xxxvii Los Angeles Municipal Code, SEC. 98.0503. TESTING AGENCIES
- xxxviii <u>https://up.codes/viewer/california/ca-building-code-2022/chapter/17/special-inspections-and-tests#1707.1</u>
- xxxix New York City, The Rules of the City of New York, § 101-07 Approved Agencies
- New York City, The Rules of the City of New York, § 101-07 Approved Agencies
- xii https://up.codes/viewer/new\_jersey/ibc-2018/chapter/17/special-inspections-and-tests#1707.1
- xlii https://www.nj.gov/dca/divisions/codes/codreg/ucc.html
- xiii https://www.ecfr.gov/current/title-24/subtitle-B/chapter-XX/part-3282/subpart-A/section-3282.14
- xiv https://www.ecfr.gov/current/title-24/subtitle-B/chapter-XX/part-3280
- xiv IBC 2021, Section 1706 Design Strengths of Materials, 1706.2 New Materials. Adopted law pursuant to IBC model code language 1706.2.
- xivi IBC 2021, Section 1707 Alternative Test Procedure, 1707.1 General Adopted law pursuant to IBC model code language 1707.1.
- xvii https://www.nspe.org/resources/issues-and-advocacy/professional-policies-and-position-statements/regulation-professional AND https://apassociation.org/list-of-engineeringboards-in-each-state-archive/
- xviii IBC 2021, Section 1706 Design Strengths of Materials, Section 1706.1 Conformance to Standards Adopted law pursuant to IBC model code language 1706.1.
- xix <u>https://iaf.nu/en/about-iaf-mla/#:~:text=it%20is%20required%20to%20recognise%20certificates%20and%20validation%20and%20verification%20statements%20issued%20by%20conformity%20assessmen t%20bodies%20accredited%20by%20all%20other%20signatories%20of%20the%20IAF%20MLA%2C%20with%20the%20appropriate%20scope</u>
- True for all ANAB accredited product evaluation agencies and all International Trade Agreements.
- https://www.justice.gov/crt/deprivation-rights-under-color-law AND https://www.justice.gov/atr/mission